



Informations techniques
Technical information

PULSA 120	MONOCHROME blanc ou vert ou rouge ou bleu White or green or red or blue			TW Tunable white	RGBW
	Puissance / Power	30W			
Température de Couleur / Color Temperature	<input type="checkbox"/> 1800K <input type="checkbox"/> 2200K <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K	TW Tunable White <input type="checkbox"/> 1800K-3000K		White <input type="checkbox"/> 1800K <input type="checkbox"/> 2200K <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K	
Flux Source / Flux Source	3000 lm				
Pilotage / Control	<input type="checkbox"/> On/Off <input type="checkbox"/> DALI <input type="checkbox"/> DMX <input type="checkbox"/> Casambi				
Angle d'éclairage / Beam Angle	<input type="checkbox"/> 12° <input type="checkbox"/> 24° <input type="checkbox"/> 40° <input type="checkbox"/> 60° <input type="checkbox"/> Elliptique <i>Elliptical</i> 10°x40° > <input type="checkbox"/> Vertical <input type="checkbox"/> Horizontal				
Alimentation / Voltage	230 VAC				
IRC / CRI	IRC 90				
Matière / Material	Aluminium				
Finition / Finish	Thermolaquage RAL au choix <i>Powder coating, custom RAL</i>				
Protection (IP - IK - Classe) / Protection	IP66 – IK10 – Classe 2				
Poids / Weight	3,2kg				
Garantie / Guarantee	5 ans / 2 years (export)				

Photométries
Beam angles

Sens de l'ellipse au choix :
Orientation of elliptical angle to be chosen:
Horizontal / Vertical

