



Informations techniques
Technical information

PULSA 180	MONOCHROME blanc ou vert ou rouge ou bleu White or green or red or blue		TW Tunable white	RGBW
	Puissance / Power	60W		
Température de Couleur / Color Temperature	<input type="checkbox"/> 1800K <input type="checkbox"/> 2200K <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K	TW Tunable White <input type="checkbox"/> 1800K-3000K		White <input type="checkbox"/> 1800K <input type="checkbox"/> 2200K <input type="checkbox"/> 2700K <input type="checkbox"/> 3000K
Flux Source / Flux Source	6000 lm			
Pilotage / Control	<input type="checkbox"/> On/Off <input type="checkbox"/> DALI <input type="checkbox"/> DMX <input type="checkbox"/> Casambi			
Angle d'éclairage / Beam Angle	<input type="checkbox"/> 12° <input type="checkbox"/> 24° <input type="checkbox"/> 40° <input type="checkbox"/> 60° <input type="checkbox"/> Elliptique <i>Elliptical</i> 10°x40° > <input type="checkbox"/> Vertical <input type="checkbox"/> Horizontal			
Alimentation / Voltage	230 VAC			
IRC / CRI	IRC 90			
Matière / Material	Aluminium			
Finition / Finish	Thermolaquage RAL au choix <i>Powder coating, custom RAL</i>			
Protection (IP - IK - Classe) / Protection	IP66 – IK10 – Classe 2			
Poids / Weight	6kg			
Garantie / Guarantee	5 ans / 2 years (export)			

Photométries
Beam angles

Sens de l'ellipse au choix :
Orientation of elliptic angle to be chosen:
Horizontal / Vertical

