



Technical Data

Puissance / Power	20 mW nominal
Alimentation / Voltage	24V DC provided w/ auxiliary power supply or D4i driver
Pilotage Radio / Radio Control	Bluetooth 5.0 - Casambi Radio Mesh 2,4GHz
Pilotage d'éclairage / Light Control	DALI 2 D4i IEC62386 – DALI DT6, DT8, PWM
Plage de Température / Temperature Range	- 40°C / + 85 °C
Plage d'humidité /humidity range	0 / 90%
Matière / Material	PBT socket / Polycarbonate dome
Montage et connecteur / Mounting and connector	Zhaga Book 18
Portée radio / Radio range	80m en champs libre ou 200m en configuration Longue portée
Nœuds max par réseau / Nodes max per network	250 for standard configuration or 60 for the long-range
Protection (IP - IK - Classe)	IP66 - IK08 - Class 3
Dimension / Size	D : 80 mm / H : 57 mm
Poids / Weight	0,060kg
Accessoire / Accessory	Rain seal

Features & Settings

100% modular options

Détection de Mouvement / Motion Detection	<input checked="" type="checkbox"/>
Programmation Calendaire / Calendar Programming	Time synchronization via Gateway or GPS RTC
Horloge Astronomique / Astronomical Clock	Time synchronization via Gateway or GPS RTC
Mise à jour à Distance / OTAP	<input checked="" type="checkbox"/>
Intégration Casambi Ecosystème / Casambi Ecosystem Integration	<input checked="" type="checkbox"/>
Application mobile (Smartphone) / App mobile Control	<input checked="" type="checkbox"/>
Plateforme de supervision distante / Remote Monitoring	Via the Casambi Cloud (native solution), integration is possible with building management software through gateways or custom development using APIs
Compatible DALI2 DT8 (Dimming & Colour changing if TW Leds)	<input checked="" type="checkbox"/>